

Additives for coatings and printing inks
DISPARLON[®]

Nov. 2, 2016

DISPARLON[®] JXL-622
(Slipping/Leveling agent)

DISPARLON JXL-622 is a silicone based slip/leveling agent. **DISPARLON JXL-622** has excellent compatibility to coatings without haze and improves slipping, scratch resistance, anti-blocking properties. It also prevents cratering, cissing and pin-hole that come from contamination taking full advantage of excellent leveling property.

ADVANTAGES

- Good leveling & DOI.
- Prevent crater & fish eye.
- Good dispersibility and stability on ageing in paint systems.

APPLICATIONS

DISPARLON JXL-622 can be used for all solvent based systems.

Especially, it is recommended to ambient cure system such as 2K urethane or lacquer paint for Wood or Plastic

INCORPORATION

Recommended levels : 0.1 ~ 1.5 % by wt on total formulation.

Method : Post addition on High speed dissolver is recommended.

TYPICAL PROPERTIES

Appearance : Colorless to light yellow liquid
Active matter : 20 % by wt.
Density : 0.95 g/cm³ (25°C)
Solvent : n-Butyl acetate / 2-Phenoxyethanol



楠本化工(昆山)有限公司

Kusumoto Chemicals (Kunshan) Co., Ltd.

NO.5 Jinfa Road, Jinxi Town, Kunshan City, Jiangsu Province, China
Zip:215300 Tel.:(86)-512-57236788