

*Additives for coatings and printing inks*  
**DISPARLON®**

Aug. 26, 2014

**DISPARLON® LHP-95**  
(Leveling/Anti-cratering agent)

**DISPARLON LHP-95** is a surface control agent based on specially prepared acrylic polymer. This product has such unique properties as to eliminate cratering caused by various kind of dirt/stain or spray mists. It is very effective in industrial coatings where a high quality film appearance is required.

**ADVANTAGES**

- Greatly improve the flow and provide excellent surface appearance.
- Eliminate cratering and film defects due to various contaminants.
- Eliminate formation of Benard-cell.
- Provide excellent re-coat property.

**APPLICATIONS**

**DISPARLON LHP-95** can be used in almost all type of solvent based systems.

**INCORPORATION**

Additive level : 0.2 ~ 0.5% by weight of finished paint.  
Preliminary test should be made to determine optimum level.  
Method : Post-addition on high speed dissolver is recommended.

**TYPICAL PROPERTIES**

Appearance : Colorless to light yellow liquid  
Non-volatile matter : 50% by weight  
Density : 0.95 g/cm<sup>3</sup>  
Solvent : Solvent naphtha



**楠本化工(昆山)有限公司**

*Kusumoto Chemicals (Kunshan) Co., Ltd.*

NO.5 Jinfa Road, Jinxi Town, Kunshan City, Jiangsu Province, China

Zip: 215300 Tel: (86)-512-57236788